



## E-06 (SPL)

### E-06 (SPL): LIQUID EPOXY RESIN SPECIAL

#### Data Sheet

**E**PIRAN-06(SPL) is a General Purpose Liquid Epoxy Resin. It does not contain any Diluents.

Curing Agents used are Aliphatic Polyamines, Polyamides, Amidoamines, Cyclo- Aliphatic Amines and modifiers of above curing agents.

PROPERTY	TEST METHOD	UNIT	GUARANTEE VALUES
Appearance	Visual	Visual	Clear Light Yellow
Epoxy Equivalent	ASTM D1652	g/eq	185 - 192
Epoxy Value	ASTM D1652	mol/100g	0.52 – 0.54
Color	ASTM 1209	Pt-Co (APHA)	Max. 50
Viscosity @ 25°C	ASTM D2983	mpas	10,000-14,000
Hydrolysable Chlorine	ASTM 1726	% wt	Max. 0.1
Non-Volatile	DIN EN ISO 3251	% wt	Min 99.3

#### ➤ APPLICATION

Adhesives, Casting, Tooling. Civil Eng. Composites. Automotive, Can and Coil Coatings. Marine and Protective Coatings, Electrical & Electronics use, Potting and Encapsulation.

Datis Inc.

Reg. No.: 318496

Affiliated to Datis Export Group



You Desire, We Export

**Datis Export Group**

**YOU DESIRE, WE EXPORT**

Follow US

On Social Networks



ONLINE on WhatsApp, Wechat, Telegram

+989123214280



INQUIRY and sending Letter of Intent (LOI)

[Sales@Datis-inc.com](mailto:Sales@Datis-inc.com)



[WWW.DATIS-INC.COM](http://WWW.DATIS-INC.COM)  
[SALES@DATIS-INC.COM](mailto:SALES@DATIS-INC.COM)

Tel: +98-21-460-92320  
WhatsApp/Wechat: +989123214280